

**Application:****SAE 100R2 AT/EN853 2SN(cloth wrapped surface)**

Mainly used for conveying of petroleum or water based hydraulic fluids in mobile, machine tool, agricultural applications etc.

**Construction:**

Tube: NBR synthetic rubber.

Reinforcement: Two layers of high-tensile steel wire braided.

Cover: NBR oil and weather resistant synthetic rubber.

**Color:**

Black, Grey, Blue, etc.

**Temperature:**

-40°C to +100°C

**Standard:** SAE/DIN

Item Code	Inner Diameter		Outer Diameter	Working Pressure		Burst Pressure		Length	Volume	Weight
	inch	mm		mm	bar	psi	bar			
P03-2SN	3/16	5.0	12.3	414	6000	1655	24000	100	0.0405	0.320
P04-2SN	1/4	6.4	15.5	400	5800	1600	23200	100	0.0514	0.370
P05-2SN	5/16	8.0	16.5	350	5075	1400	20300	100	0.0612	0.412
P06-2SN	3/8	10.0	19.5	331	4800	1324	19200	100	0.0784	0.530
P08-2SN	1/2	12.5	22.5	276	4000	1103	16000	100	0.0833	0.640
P10-2SN	5/8	16.0	25.5	250	3630	1001	14520	50	0.074	0.770
P12-2SN	3/4	19.0	29.5	215	3120	860	12480	50	0.0833	0.960
P16-2SN	1	25.0	38.1	165	2400	662	9600	50	0.1445	1.350
P20-2SN	1 1/4	32.0	48.0	125	1820	502	7280	20	0.209	2.050
P24-2SN	1 1/2	38.0	55.0	90	1310	361	5240	20	0.2509	2.511
P32-2SN	2	51.0	68.6	80	1160	320	4640	20	0.3796	3.165

**Office Address:**

B-702  
Hangzhou Smart Industrial Park  
No. 857 Wenyixi Rd.  
Hangzhou 310030  
CHINA

**Registered office**

Hangzhou

**Internet Address**

[www.flexiblerubberhoses.com](http://www.flexiblerubberhoses.com)

**Cellphone**

+86-136-6663-2043

**Wechat(WhatsApp)**

+86-136-6663-2043

**Email (Janet Yao)**

[ps005@parshun.com](mailto:ps005@parshun.com)

**Skype**

paishun005